



UT352

UT352 sound level meter can measure noise level and output results in dB. A or C weighted modes can be selected depending on the application. UT352 consume very little power and can continuously work up to 20 hours. They are suitable for industrial and environmental sound level measurements.

Specifications	Range	UT352
Certificates	CE, UKCA	
Range	30~130dB	
Accuracy	±1.5dB	
Frequency	31.5Hz~8000Hz	
Frequency weighting	A&C	
Sampling rate (Fast)	8 times/s	
Sampling rate (Slow)	1 time/s	
Data storage	63	
Analog outputs (AC)	0.707Vrms full scale; Output impedance: around 600Ω	
Analog outputs (DC)	2Vrms full scale; 10mV/dB; Output impedance: around 100Ω	

Features

Powered by batteries or external power source

Data hold

LCD backlight

A (ear)/C (machine) weighted modes

Auto power off (cancelable)

63 sets of data storage

AC/DC analog signal output

Simulated analog bar

Manual/auto range selectable

Analog bar graph: 30~130dB

Low battery indication: ≤4.8V

MAX/MIN

High/low alarm

Characteristics

Standard accessories Windscreen, leather box, English manual

Power 1.5V battery (LR6) x 4

Display 53 x 41mm

Product size 273 x 70 x 39mm

Product net weight 330g

Standard individual packing Gift Box

Standard quantity per carton 10pcs

Standard carton measurement 670 x 415 x 120mm

Standard carton gross weight 7.3kg